


CeLAN Touch Screen


DS-Ce-TS Rev A



The CeLAN Touch Screen provides a 5.6" Color LCD (liquid-crystal display) to provide the user with complete on-site system programming and operation control of the Protector System. The 5.6" Color LCD provides a graphical user interface to display visual status messages for the entire system. The display identifies any programmed location so the user can determine where an alarm, trouble, or open-sensor condition exists. Location names or zone/sensor text are displayed allowing for easy identification.





Zone/sensor names can be entered into the system using the on-screen QWERTY keyboard or by using a traditional serial keyboard and the CINCH-On PS2 Keyboard Interface. Sensor names are stored in the panel, which eliminates the need for downloading sensor text from one touch screen to another. Display backlighting lights up after the



Features

- CeLAN AES encrypted technology for security, easy setup and enhanced performance
- 5.6" Color Touch Screen with protective display overlay and Lexan shield
- Simple, easy to use Graphical User Interface
- Four pass code entry options
- Scrambled/Standard QWERTY
- Scrambled/Standard 12-key Numeric
- Built-in 'on-line' help and diagnostic screens
- Remote keyboard option for use in programming using the CINCH-On PS2 Keyboard Interface.
- Two hardware input zones per module
- Five (5) state zones:
 - Open Circuit
 - Supervised Circuit (3k EOL)
 - Short Circuit
 - Ground Fault High
 - Ground Fault Low
- Surface or recessed mounting options.
- 'CINCH Stick' Field Upgradeable software



Open Zone Condition



Scrambled QWERTY Keyboard

CeLAN Touch Screen

Specifications

Power Requirements:

- Input: 12 VDC (8 VDC min, 14 VDC max)
- Output: N/A
- Current Draw: 240mA standby, 500mA max

Dimensions: 8.26" x 5.24" (LxW)

Environmental:

- Operation Temp: 32 to 120 F (0 to 49 C)
- Humidity: 90% relative humidity

Storage Temp:

- -30 to 140 F (-34 to 60 C)

Inputs:

- 2 hardwired supervised inputs

CELAN Devices per System:

- 100 CeLAN Devices

Accessories:

- Face Plate –
- Backbox –
- Mounting Plate –
- Faceplate Decal – RC-CeTSL
- Touch Screen Assembly – RC-TS

Listings:

- UL 1076
- FCC Part 15
- FIPS 197 Cert # 1125

Touch Screen Replacements



Touch Screen Assembly

RC-TS



Face Plate



Face Plate Decal

RC-CeTSL



Back Box



Mounting Plate

Ordering

Control Panel

PCU-IDS Protector Panel

Touch Screen

Ce-TS Touch Screen

Expansion Modules

Ce-2ZI 2 Zone Input

Ce-8ZI 8 Zone Input

Ce-4RO 4 Relay Output

Ce-24ZI 24 Zone Input

Communication Modules

Ce-FC-N Fiber Conversion

Ce-TCP/IP Network Module

Ce-FC-ER Fiber Conversion

CeLAN Modules

Ce-DS938Z Motion

Ce-DS308 Motion

Ce-DSISC Motion

Ce-M3ZS HSS L2 Contact

Ce-M1ZRS Recessed Contact

Ce-1076DRS Recessed Contact

Ce-1076HRS Recessed Contact

Ce-U1Z Universal 1 Zone

Ce-WF2ZI Wellsfargo Contact

Ce-U2Z Universal 2 Zone

Receivers

Ce-AESR-IDS AES Receiver

CeLAN Accessories

CO-CSU Cinch Stick

CO-PS2KI Keyboard Module

CO-T-P Panel Tester

CO-T-8Z 8 Zone Tester

CO-T-4R 4 Relay Tester

CO-T-Printer Printer Tester

CO-PRSI Siren Supervision

Ce-EX Expansion Module

Power

ACC-24T-100 Transformer

ACC-B12-18 18Ahr Battery

ACC-B12-7 7Ahr Battery

ACC-6P Power Cord

E-CB Termination Box

Accessories

L-M-KD Panel Lock

L-M-KA Panel Lock

ACC-CFC-S Fiber Cable

L-S Standard Panel Lock

ACC-CFC-MM Fiber Cable

S-ET Panel Tamper

Enclosures

E-P Panel Enclosure

E-P-Kit

E-CP Plastic Enclosure

E-PA Accessory Enclosure

E-PA-Kit

E-PA-S Small Accessory Enclosure

E-PA-S-Kit

For more information: www.cinchsystems.com

Cinch Systems

10275 43rd St NE, Ste 300

St Michael, MN 55379

1-763-497-1059

